



IPSO®

Drying cabinet

DC 4



Features

- Flexible construction allows hanging bars to slide easily forward for easy access to garments or down for more space
- Easy to install; the evacuating channel is connected to the ventilation system and the humid air is transported out of the room
- All electrical components are placed on the top which makes it easy to maintain
- Pull-out hanging system
- 3 temperatures; high, normal, low
- Energy efficient
- Timer adjustable up to 4 hours
- Overheat protection
- IP 24 classification. CE-approved
- The door can be ordered right- or left-hinged

Options

- Baskets to drip dry on a flat surface
- Hangers for small items (door frame)

Markets

Day care center, Schools, Road workers dressing room, Ships, Airports, Ski resorts, Campings, Security



DC4

Loading capacity	4 kg/8,8 lbs
Drying capacity	17 g/min*
Hanging length	16/52,5 m/feet
Drying time, economy 30° C	180 min*
Drying time, express 45° C	120 min*
Heating effect	1,5 kW
Total effect	1,535 kW
Energy consumption economy /kg	0,5 kWh
Energy consumption express /kg	0,6 kWh
ELECTRICAL CONNECTIONS	
Electrical connection	1N, 230 V, 50 Hz
Fuse	10 A
Total effect	1,535 kW
Heating elements	1,5 kW
AIR CONNECTIONS	
Outlet exhaust	ø 100 mm/3,94 inch
Outlet air flow	50 m³/h
Pressure drop	60 max Pa
Dewatering capacity	17 g/min
SOUND LEVEL	
Airborne sound level	60 dB(A)
SHIPPING DATA	
Net	61 kg/134,5 lbs
Crated	4 kg/8,8 lbs
Shipping data net	65 kg/143 lbs
Shipping volume	0,2 m³
OPTIONAL EXTRAS	
Air exchanger 1 vent.,125 mm/4,9 inch	Part number 141009
Air exchanger 2 vent.,160 mm/6,3 inch	Part number 141018
DIMENSIONS	
Width	595 mm/23,4 inch
Depth	615 mm/24,2 inch
Height	1915 mm/75,4 inch

*Valid for high-spinned textiles.