



IHP190 - IHP250 - IHP285 - IHP345

Industrial tumble dryers with heat pump

INDUSTRIAL
BY DESIGN

Features

- Heat pump
- Standard stainless steel drum with large diameter
- Easy-to-use microprocessor (Easy)
- Combination of Radial and Axial airflow concept:
 - Maximal heat transfer
 - Low energy consumption
 - Short drying time
- Large door opening for easy loading and unloading
- Self cleaning lint screen

Options

- Coin operated version
- Reversing drum
- Full Control programmer (Flex)
- Residual moisture control:
 - Safe drying of delicate linen
 - Humidity detection in %
 - Ideal in combination with wet cleaning
 - ideal for dry cleaners, fire depts
 - available on Easy and Flex Control
- Stainless steel front



HEAT PUMP



STANDARD STAINLESS
STEEL DRUM



ENERGY
EFFICIENT

IHP190 - IHP250 - IHP285 - IHP345

TYPE		IHP190	IHP250	IHP285	IHP345
CAPACITY					
Drum capacity	kg/lb	9/20	11/25	13/30	16/35
Drum volume	l	190	250	285	345
Drum diameter	mm	Ø 760	Ø 760	Ø 760	Ø 760
DRYING AVERAGE					
	g/min	122	126	120	120
MOTORS					
Fan	kW	0,20	0,20	0,20	0,20
Drive	kW	0,25	0,25	0,25	0,25
HEAT PUMP					
Electrical connection		3 × 380-415V 50Hz +N (standard)			
Energy	kW	2,9	2,9	2,9	2,9
PROGRAMMER					
Easy control - antivandal		standard	standard	standard	standard
Full control	kPa	available	available	available	available
DIMENSIONS					
Size HxWxD	mm	1465 × 795 × 1275	1680 × 795 × 1525	1680 × 795 × 1615	1680 × 795 × 1735
TRANSPORT DATA					
Gross weight	kg	305	360	400	400
Net weight	kg	290	350	360	375

Energy consumption comparison

CONVENTIONAL DRYER vs. **HEAT PUMP DRYER**

